

0.6/2.8 AF

Video Cable 75 Ω



Application

Video cables are primarily used in closed circuit TV systems and in several studio applications for transmission of image signals.

Standards

For analogue and digital video signals (Composite, component, SDI, SDV, SDTI, HDTV)

Flame resistance

PVC: IEC 60332-1
 FRNC: IEC 60332-1, IEC 60754, IEC 61034
 FRNC-C: additionally IEC 60332-3 C

Construction

Inner conductor	solid copper wire, bare, diameter 0.6 mm
Insulation	Foam-PE, diameter 2.8 mm
Outer conductor	Al-PETP-Al-foil under tinned copper braid, diameter 3.4 mm
Sheath	FRNC or PVC, diameter 4.5 mm green, RAL 6018
Printing	for FRNC: DRAKA - 0.6/2.8 AF - 75 Ω ± 1% - HDTV FRNC for PVC: DRAKA - 0.6/2.8 AF - 75 Ω ± 1% - HDTV

Electrical properties

at 20°C

DC resistance	Inner conductor	61 Ω/km
	Outer conductor	17 Ω/km
Mutual capacitance		52.8 pF/m
Characteristic impedance		75 Ω ± 0.75 Ω
Velocity ratio		78 %
Screening factor		> 100 dB

0.6/2.8 AF

Electrical data

at 20°C

Attenuation (dB/100m)		Return loss (dB)	
Frequency (MHz)		Frequency (MHz)	
1	1.1	50 – 300	≥ 26
3	1.9	300 – 3000	≥ 22
5	2.4	3000 – 3500	≥ 18
10	3.1	3500 – 5000	≥ 15
30	5.4		
100	10.5		
200	14.8		
300	17.9		
500	23.1		
800	29.3		
1000	32.8		
1500	40.4		
2250	49.8		
3000	59.3		
3500	66.3		
4000	71.5		
4500	77.0		
5000	82.8		

Technical data

Product code	Type	Weight kg/km	Standard delivery length m	Drum size KTG/ring	Copper content	Tensile force N	Bending radius mm	Storage
1002160 CT2738600	0.6/2.8 AF PVC green	27	1000	051	14	60	25	inside
1002161 CT2738601	0.6/2.8 AF PVC black	27	1000	051	14	60	25	inside
1002162 CT2738602	0.6/2.8 AF PVC blue	27	1000	051	14	60	25	inside
1002164 CT2738604	0.6/2.8 AF PVC violett	27	1000	051	14	60	25	inside
1002167 CT2738610	0.6/2.8 AF PVC green + meter marking	27	1000	051	14	60	25	inside
1002203 CT2850202	0.6/2.8 AF FRNC-C gn	28	1000	051	14	60	25	inside

[PRODUCT CODE TABLE]

© PRYSMIAN GROUP 2011, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.